

# Label slitting machine

## MÜSONIC3

for cutting labels to width with very  
fine-cut edges from supply rolls



# MÜSONIC3

## General features

The MÜSONIC3 cuts label strips ultrasonically taken from supply rolls to the required width for optimal further processing. The cutting area is compressed by a selvedge pre-compactor prior to cutting, leading to fine edges free from filaments.

All fusible synthetic yarns and blends with max. 66% proportion of cotton can be processed. Modern machine control with touch-screen for rapid and simple programming also permits data to be stored specific to the product.

## Advantages

- Unvarying cut edge quality
- Selvedge pre-compactor for optimal cutting preparation, pressure continuously adjustable
- Minimum waste
- Stable, compactly wound label rolls for optimal downstream processing
- No forerunner needed thanks to precise infeed and offtake
- Simple handling, speedy knife adjustment
- Long sonotrode life owing to low compressive force
- Cutting quality can be verified during cutting
- Sonotrode amplitudes individually variable with automatic adaptation to speed
- High productivity
- Ergonomic design
  - Cutting elements at eye level
  - Running direction from rolls rear to front: better visual supervision
- Low maintenance costs
- Modest space requirement
- Pneumatic winding axles

## Options

- Thermofixing device 200 mm
- Core diameter 40 mm or 50 mm
- Ultrasonic welding device
- External winders (BWW / BWF)



Supply of label ribbon from roll

## Technical data

|                               |   |
|-------------------------------|---|
| Minimum cutting width         | 10 mm (Option: 6 mm)                      |
| Machine speed                 | 1,5 – 60 m/min                            |
| Sonotrode rating              | standard 2 sonotrodes of 1200 W at 30 kHz |
| Maximum supply roll width     | standard 280 mm                           |
| Maximum supply roll diameter  | 500 mm                                    |
| Standard Core diameter        | 75 mm                                     |
| Cutting wheel duty cycle      | about 3000 m before readjustment          |
| Space requirement (PZ 5074/A) | 1045 x 1100 x 2300 mm (W x D x H)         |

Copyright © 2017 by Jakob Müller AG Frick  
5070 Frick Switzerland

Printed in Switzerland. All rights reserved.

No part of this publication may be reproduced by any means, nor translated, nor transmitted into a machine language without the written permission of the publisher.

This leaflet contains photos and technical data for information only, without contractual engagement.

**Fascination of Ribbons and Narrow Fabrics  
Innovation in Machinery**

Rep.:



**Jakob Müller AG Frick**  
5070 Frick Switzerland  
Tel +41 62 8655 111  
Fax +41 62 8655 777  
www.mueller-frick.com

